



Satellite Mobile Dispensing System

Low-cost, portable dilution device

The Satellite mobile dispensing system offers a low-cost, portable means of accurately diluting concentrated cleaning products for use in mop buckets, sinks, auto scrubbers, tanks, and other containers.

- Mobile: Take it anywhere! It goes anywhere you can find water and carry your chemical container.
- Adjustable product connection allows use with F-style and round containers, 1/2 gallon and gallon, 2 liter and 4 liter. Use the forward connection position for F-style containers, the rear connection position for round containers.
- Fits virtually any cap: The Satellite comes with a 38mm cap connection, industry standard. If you have a special size cap - send it to us and we'll assemble a model for you (minimums apply).

All Satellite mobile dispensing systems include:

- Hydro's E-Gap eductors for backflow protection through use of an elastomeric sleeve. (ASSE 1055B Approved)
- Patented AccuPro pressure regulation technology: No more fluctuating dilution rates as water pressure varies. With the new AccuPro technology, your dilution rate is always consistent, across a wide range of pressures.





The Hydro Satellite Series features:

- Handy On/Off trigger: Easy to operate with one hand, no matter how large or small your hands are.
- Convenient locking button: Activate the Satellite with the On/Off trigger, then lock it in the "On" position - all with one hand!
- Overmolded handle: For safe, sure gripping.
- A Built-in hanger: Allows you to quickly and easily attach the Satellite to your bucket or scrubber.
- Adjustable velcro strap for container stability: Allows you to secure either an F-style or round bottle to the Satellite for better balance.
- Multiple dilution rates: Pick from 14 different dilution rates using the metering tips included with the Satellite. (Additional tips available)
- Easy connections to water source: Use one of the optional connectors for quick and easy access to almost any water source.

Satellite Mobile Dispensing System Models

Model	Description	Flow Rate (GPM)	Approximate Dilution Range	
			Max	Min
5843	Initial container position set-up for F-style containers	3.5	300:1	10:1
5844	Initial container position set-up for round containers	3.5	300:1	10:1
5845	Satellite "F" style, rite connect	3.5	300:1	10:1
5846	Satellite gallon, rite-connect	3.5	300:1	10:1
5848	Satellite gallon, SMP feed	3.5	300:1	10:1

Water source connectors:



Model
5820



Model
5830



Model
5840



Hydro Systems
3798 Round Bottom Road
Cincinnati, OH 45244

Phone 513.271.8800
Toll Free 800.543.7184
Fax 513.271.0160
Web hydrosystemsco.com